

Soflux OX

hospital quality, cool and comfortable

Soflux OX (OX- Oxford PU) is a 200-210 denier Oxford Nylon fabric with a polyurethane coating. The product is designed for applications where an anti-microbial, fluid-proof healthcare fabric is required. Soflux OX is an ideal fabric for University housing as it offers superior student comfort (breathability) and clean ability.

Weight:	4.6 oz. / sq. yard
Coating:	Urethane; 1.25 oz. minimum
EPA Registration:	Bacteriostat 10466-28 Fungistat 10466-23
Antibacterial:	AATCC Method 147-1988 Contact Inhibition, Staphylococcus aureus 99%+
Antifungal:	AATCC Method 30-1988 Contact Inhibition Aspergillus niger 99%+
Flame Resistance:	NFPA 701; CAL 117; BS EN 1031-1, 1994; BS EN 1021-2, 1994; BS EN 5852, 1990 (crib 5): PASS
Cigarette Ignition:	FF4-72/16CFR, Part 1632: PASS
Moisture Vapor Transmission:	ASTM E96/BW: 100 g / m ² / 24hr
Hydrostatic Burst (PSI):	Federal Standard 191-5512: 200 lbs.
Tear Strength:	Federal Standard 191-5134: Warp: 4.6 lbs.; Fill: 4.0 lbs.



310 Watline
Mississauga, Ontario L4Z 1P4 Canada
905 • 890 • 7990 Fx: 905 • 890 • 7991
www.frsystems.ca